

RoClean P112 is a powdered cleaner designed to remove silt and organic foulants such as colloidal silica, clays, organic colour and bacterial slime from thin film composite membranes. RoClean P112 is buffered to prevent the pH limits of a membrane being exceeded in the event of misapplication. RoClean P112 should not be used on cellulose acetate membranes, as irreversible damage can occur.

Performance

RoClean P112 offers a variety of performance benefits:

- Compatible with the major membrane suppliers.
- Superior results in the removal of organic and colloidal foulants, especially when compared to generic formulations.
- Used when high pH cleaning required for heavy fouling.
- Contains a specialised blend of buffers and other components to dissolve organic foulants, and disperse colloidal particles
- Highly buffered to resist pH changes during the cleaning process.
- Can be used in conjunction with other applicable cleaners as shown in the Avista cleaner selection guide.

Avista Technologies (UK) Ltd Waterside House PO Box 28612 Edinburgh, EH14 5ZL United Kingdom

Tel +44 (0)131 449 6677 Fax +44 (0)131 449 5599 Email sales@avistatech.co.uk Web www.avistatech.co.uk

Instructions for Use:

For severe fouling, RoClean P112 should be applied at a nominal strength of 2% w/v. For milder fouling select P111 or L211.

The cleaning solution should be recirculated at the flow rate recommended by the membrane manufacturer, taking care not to exceed the guidelines for pressure. Avista Technologies recommend the following flowrates for cleaning spiral wound elements:-

Element Diameter	Flowrate
4" (100mm)	40 lpm
8" (200mm)	150 lpm

Temperature:

Where possible, apply the cleaning solution at the maximum temperature recommended by the membrane manufacturer.

Packaging:

RoClean P112 is available in 20Kg pails. Other packaging is available on request.

Property	Analysis
Appearance	Pale Cream Powder
pH at 2% solution	12 – 12.5
Density	1.2 kg/ litre